



EN ISO 20345:2011



ENDURANCE  
**MONTANA**

**81156-22L**

**S3 WR SRC**

**Size:** 36-48  
**Weight:** 750 gr.

**Fit:** 11

**Working Environment:**  
Building, Farming and Gardening,  
Mountains



**FEATURES**

**UPPER**

Greased Nubuk Dakar Leather  
Hydro

**LINING**

Soft Full Grain Leather  
3D Air circulation 320 gr.

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

Dual insulation

**TOE CAP**

CTC- Composite Toe Cap

**RESISTANCE TO PERFORATION**

Zero(K) Perforation resistant

**TYPE**

Half-knee Boot

**SOLE**

**PU DUAL-DENSITY SRC**

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

**TECHNOLOGIES**

**Removable Insole**



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



**Protection elements**

**ZERO(k)**

ANTIPERFORATION

**STEEL TOECAP**

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



**Lateral stability**

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**

**WED**

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**

**DUALMICRO**  
DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



**SRC (SRA+SRB)**



		SOLE B1 PU - PU
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	<b>0.52</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	<b>0.23</b>
		<b>0.18</b>

EN ISO 20344:2011