



EN ISO 20344:2011



ENDURANCE

**LAND**

**81153-18L**

**S3 SRC**

**Size:** 36-48

**Weight:** 670 gr.

**Fit:** 11

**Working Environment:**

Building, Wood-metal carpentry, Farming and Gardening, Multipurpose



## FEATURES

### UPPER

Grain Leather Hydro 1,8-2,0 mm  
Pu Coated Leather 1,8-2,0 mm  
Soft Full Grain Leather Hydro

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### SOLE

Blowfit

### TOE CAP

CTC- Composite Toe Cap

### RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

### TYPE

Low Shoe

### SOLE

#### PU DUAL-DENSITY SRC

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

## TECHNOLOGIES

### Removable Insole

## BLOWFIT

The upper part in FLYFIT, directly in contact with the foot, means transpiration and comfort. Under the heel, a support in EVA keeps the shape and resistance over time, efficiently supporting the bodyweight.



### Protection elements

#### ZERO(k)

ANTIPERFORATION



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.



### Lateral stability

## dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

## STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features

## WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other

## DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



## SRC (SRA+SRB)



SOLE 81  
PU - PU

| SRA<br>CERAMIC<br>+<br>DETERGENT<br>SOLUTION | FLAT<br>≥0.32<br>HEEL<br>(CONTACT ANGLE 7°)<br>≥0.28 | 0.52         |
|--|--|--------------|
| SRB<br>STEEL<br>+<br>GLYCEROL                | FLAT<br>≥0.18<br>HEEL<br>(CONTACT ANGLE 7°)<br>≥0.13 | 0.23<br>0.18 |

EN ISO 20344:2011