




EN ISO 20345:2011 


HORIZON
STEEL
52440-00L

S3 SRC

Size: 36-48
Weight: 770 gr.

Fit: 10,5

Working Environment:
Building, Wood-metal carpentry,
Farming and Gardening,
Multipurpose





FEATURES

- UPPER**
Grain leather Hydro 1,8-2,0 mm
Reflex insert
- LINING**
Breezy 3D, two-layers
combination
- INSOLE**
Climaction-Fit 337
- TOE CAP**
Steel Toe Cap
- RESISTANCE TO PERFORATION**
Steel Plate
- TYPE**
Ankle boot

SOLE
PU DUAL-DENSITY SRC
Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.



SRC (SRA+SRB)

				SOLE 52 - 53 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.36	0.42	EN ISO 20344:2011
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19	0.14	

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements
STEEL PROTECTION

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit. Stainless steel Plate resistant puncture with acid-resistant paint.




Lateral stability
dynamic control technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



Torsional stability
STABIL•ACTIVE

It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUAL MICRO DWT WICBO
Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.